LOW PRESSURE REGULATOR

Model with safety relief valve incorporated, flow rate 10 kg/h

Product informations

Low pressure regulator with safety relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	10 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	0,5 ÷ 4 BAR
OUTLET PRESSURE	22 - 50 MBAR
CONNECTIONS	• IN 1/4" F - OUT 1/2" F (***SKU E820***) • IN 1/2" F - OUT 1/2" F (***SKU E821***)

SKU	MODEL	PRICE
0000000E820	LOW PRESSURE REGULATOR - IN 1/4" F OUT 1/2" F - FLOW RATE 10 KG/H	€32.5 VAT EXCLUDED
0000000E821	LOW PRESSURE REGULATOR - IN 1/2" F OUT 1/2" F - FLOW RATE 10 KG/H	€32.5 VAT EXCLUDED

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Low Pressure Regulator







Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net