



Catalogues and Products > Heating > Lpg regulators for domestic use, high and low pressure > **Low Pressure Regulator**

LOW PRESSURE REGULATOR

Model with safety relief valve incorporated, flow rate 12 kg/h

Product informations

Low pressure regulator with safety relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	12 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	1,5 BAR
OUTLET PRESSURE	25 ÷ 45 MBAR
CONNECTIONS	<ul style="list-style-type: none"> • IN 1/4" F - OUT 1/2" F (<i>SKU 900</i>) • IN 1/2" F - OUT 1/2" F (<i>SKU 905</i>)
MATERIALS	<ul style="list-style-type: none"> • DIE CASTING BODY AND COVER: ZAMAK EN 1774 • DIAPHRAGM AND OTHER RUBBER PARTS: NBR • REGULATOR LEVER, SPRING PRESS AND DIAPHRAGM HOLDER IN DIE CASTING ZAMAK EN 1774 • SPRINGS: C85 STEEL WITH ZINC-COATING TREATMENT • DIAPHRAGM WASHER AND SPRING PRESS: UNI EN 10130 IRON WITH ZINC-COATING TREATMENT



Low Pressure Regulator

SKU	MODEL	PRICE
00000000900	LOW PRESSURE REGULATOR - IN 1/4" F OUT 1/2" F	€58.7 VAT EXCLUDED
00000000905	LOW PRESSURE REGULATOR - IN 1/2" F OUT 1/2" F	€74.05 VAT EXCLUDED

