LOW PRESSURE REGULATOR

Model with safety relief valve incorporated, flow rate 12 kg/h

Product informations

Low pressure regulator with safety relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	12 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	1,5 BAR
OUTLET PRESSURE	25 ÷ 45 MBAR
CONNECTIONS	• IN 1/4" F - OUT 1/2" F (***SKU 900***) • IN 1/2" F - OUT 1/2" F (***SKU 905***)
MATERIALS	• DIE CASTING BODY AND COVER: ZAMAK EN 1774 • DIAPHRAGM AND OTHER RUBBER PARTS: NBR • REGULATOR LEVER, SPRING PRESS AND DIAPHRAGM HOLDER IN DIE CASTING ZAMAK EN 1774 • SPRINGS: C85 STEEL WITH ZINC-COATING TREATMENT • DIAPHRAGM WASHER AND SPRING PRESS: UNI EN 10130 IRON WITH ZINC-COATING TREATMENT

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Low Pressure Regulator

SKU	MODEL	PRICE
00000000900	LOW PRESSURE REGULATOR - IN 1/4" F OUT 1/2" F	€58.7 VAT EXCLUDED
00000000905	LOW PRESSURE REGULATOR - IN 1/2" F OUT 1/2" F	€74.05 VAT EXCLUDED





Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net