



Catalogues and Products > Heating > Lpg regulators for domestic use, high and low pressure > **Low Pressure Regulator**

LOW PRESSURE REGULATOR

Economic model equipped with safety relief valve incorporated, flow rate 7 kg/h

Product informations

Economical type low pressure regulator, equipped with relief safety valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	7 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	0,5 ÷ 11 BAR
OUTLET PRESSURE	20 ÷ 50 MBAR
CONNECTIONS	IN 1/4" F OUT 1/2" F
MATERIALS	<ul style="list-style-type: none"> • BODY AND COVER: ZINC ALLOY (ZAMA) • BODY PROTECTED BY GALVANIC TREATMENT (YELLOW ZINC PLATING) • COVER PROTECTED BY EPOXY POWDER COATING • COMPONENTS: NBR RUBBER, COMPLIANT WITH EN 549 RULE



Low Pressure Regulator

SKU	MODEL	PRICE
00000000750	LOW PRESSURE REGULATOR - IN 1/4" F OUT 1/2" F - FLOW RATE 7 KG/H	€31.2 VAT EXCLUDED

