



Catalogues and Products > Riscaldamento > Regolatori Gpl Alta e Bassa Pressione per Applicazioni Civili-industriali > **Low Pressure Regulator**

## LOW PRESSURE REGULATOR

Model with safety relief valve incorporated, flow rate 20 and/or 40 kg/h

### Product informations

Low pressure regulator for LPG with safety relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

### Technical Features

<b>TYPES OF GAS</b>	LPG
<b>FLOW RATE</b>	<ul style="list-style-type: none"> <li>• 20 KG - <b>SKU 1000</b></li> <li>• 40 KG - <b>SKU 1100</b></li> </ul>
<b>OPERATING TEMPERATURE</b>	- 20°C ÷ + 50°C
<b>INLET PRESSURE</b>	<ul style="list-style-type: none"> <li>• 0,5 ÷ 7,5 BAR - <b>SKU 1000</b></li> <li>• 0,5 ÷ 2 BAR - <b>SKU 1100</b></li> </ul>
<b>OUTLET PRESSURE</b>	<ul style="list-style-type: none"> <li>• ADJUSTABLE 25 ÷ 45 MBAR - <b>SKU 1000</b></li> <li>• 30 MBAR - <b>SKU 1100</b></li> </ul>
<b>OVERFLOW VALVE CALIBRATION</b>	75 MBAR
<b>CONNECTIONS</b>	<ul style="list-style-type: none"> <li>• IN 1/2" F - OUT 3/4" F - <b>SKU 1000</b></li> <li>• IN 3/4" F - OUT 1" F - <b>SKU 1100</b></li> </ul>
<b>OVERFLOW VALVE CONNECTION</b>	G 1/4"
<b>MATERIALS</b>	<ul style="list-style-type: none"> <li>• BODY AND COVER: ALUMINUM ALLOY</li> <li>• DIAPHRAGM AND GASKETS: LPG RESISTANT ELASTOMER</li> </ul>



## Low Pressure Regulator

<b>DIMENSIONS</b>	<ul style="list-style-type: none"> <li>• 177,5 X 126,4 X 136,9 MM (LXHxD)</li> <li>• 227,7 X 172,8 X 188 MM (LXHxD)</li> </ul>
-------------------	--

SKU	MODEL	PRICE
00000001000	LOW PRESSURE REGULATOR - IN 1/2" F OUT 3/4" F - FLOW RATE 20 KG/H	€186.4 VAT EXCLUDED
00000001100	LOW PRESSURE REGULATOR - IN 3/4" F OUT 1" F - FLOW RATE 40 KG/H	€365.45 VAT EXCLUDED

