



Catalogues and Products > Riscaldamento > Regolatori Gpl Alta e Bassa Pressione per Applicazioni Civili-industriali > **Low Pressure Regulator**

LOW PRESSURE REGULATOR

Model with safety relief valve incorporated, flow rate 20 and/or 40 kg/h

Product informations

Low pressure regulator for LPG with safety relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	<ul style="list-style-type: none"> • 20 KG - SKU 1000 • 40 KG - SKU 1100
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	<ul style="list-style-type: none"> • 0,5 ÷ 7,5 BAR - SKU 1000 • 0,5 ÷ 2 BAR - SKU 1100
OUTLET PRESSURE	<ul style="list-style-type: none"> • ADJUSTABLE 25 ÷ 45 MBAR - SKU 1000 • 30 MBAR - SKU 1100
OVERFLOW VALVE CALIBRATION	75 MBAR
CONNECTIONS	<ul style="list-style-type: none"> • IN 1/2" F - OUT 3/4" F - SKU 1000 • IN 3/4" F - OUT 1" F - SKU 1100
OVERFLOW VALVE CONNECTION	G 1/4"
MATERIALS	<ul style="list-style-type: none"> • BODY AND COVER: ALUMINUM ALLOY • DIAPHRAGM AND GASKETS: LPG RESISTANT ELASTOMER



Low Pressure Regulator

DIMENSIONS	<ul style="list-style-type: none"> • 177,5 X 126,4 X 136,9 MM (LXHxD) • 227,7 X 172,8 X 188 MM (LXHxD)
-------------------	--

SKU	MODEL	PRICE
00000001000	LOW PRESSURE REGULATOR - IN 1/2" F OUT 3/4" F - FLOW RATE 20 KG/H	€195.75 VAT EXCLUDED
00000001100	LOW PRESSURE REGULATOR - IN 3/4" F OUT 1" F - FLOW RATE 40 KG/H	€383.75 VAT EXCLUDED

