



Catalogues and Products > Heating > High and Low Pressure Lpg Regulators for Civil-industrial Applications > **First Stage Regulator Mod. AP 40**

FIRST STAGE REGULATOR MOD. AP 40

Model with pressure gauge, safety valve and external setting, flow rate 20-40 kg/h

Product informations

First stage high pressure regulator **Mod. AP 40**, equipped with pressure gauge, safety valve and external setting; designed to be connected directly to the tank or cylinder, reducing the pressure to an intermediate pressure towards a second stage regulator.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	20-40 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	2,5 ÷ 16 BAR
SAFETY VALVE SETTING	4 BAR
PRESSURE GAUGE RANGE	0 - 4 BAR
OUTLET PRESSURE	0,5 ÷ 2 BAR - EXTERNAL SETTING
CONNECTION	IN LEFT NUT W20LH-25-UN - OUT 3/8" F
MATERIALS	<ul style="list-style-type: none"> • BODY AND COVER: ALUMINUM ALLOY • DIAPHRAGM AND SHUTTER: HYDROCARBON RESISTANT SYNTHETIC RUBBER



First Stage Regulator Mod. AP 40

SKU	MODEL	PRICE
00000002812	HIGH PRESSURE REGULATOR MOD. AP 40 - IN LEFT NUT W20LH-25-UN - OUT 3/8" F - FLOW RATE 20-40 KG/H	€141.35 VAT EXCLUDED

