HORIZONTAL REGULATOR FOR DOMESTIC USE

Model with external setting, flow rate 1 kg/h

Product informations

Horizontal low pressure regulator for domestic use, designed to maintain and manage gas flows within the domestic contest.

Technical Features

TYPES OF GAS	LPG
FLOW RATE	1 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	0,3 ÷ 7,5 BAR
OUTLET PRESSURE	20 ÷ 60 BAR - EXTERNAL SETTING
CONNECTION	IN NUT CH25 H16 - OUT LPG HOSE NOZZLE CONNECTOR

SKU	MODEL	PRICE
00000000201	REGULATOR FOR DOMESTIC USE - IN NUT CH25 H16 - OUT LPG HOSE NOZZLE CONNECTOR - FLOW RATE 1 KG/H - EXTERNAL SETTING	**€8.3 VAT EXCLUDED**

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Horizontal Regulator for Domestic Use









Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net