



Double Rotating Union

Catalogues and Products > Air-Conditioning > Fittings in Copper and Brass > **Double Rotating Union**

DOUBLE ROTATING UNION

FF fitting for air conditioning pipes

Product informations

Double rotating union for refrigeration and air-conditioning systems comply to DIN 8912 standard, SAE J513 standard, U.S. Military Standards MS-35867 through MS35873 inclusive, MS-35919, MS-24815 and MS-16993.

Product features

- manufactured from brass forgings (*compliant to standards EN 12420 and EN 12165*) or drawn brass rod (*compliant to standard EN 12164*) which eliminate the possibility of leakage due to porosity in the material
- accurately machined and fully protected against damage during shipping, handling and storage to assure tight leakproof joints
- smooth interior finish provides unrestricted flow and reduced pressure drop
- smooth sealing surfaces finish and tight tollerances to eliminate the risk of leakage
- risk category as per Art. 4 Par. 3 of Directive PED 2014/68/EU
- suitable for HCFC, HFC and R744 (CO₂) refrigerants. *Not suitable for ammonia*

Technical Features




Double Rotating Union

SKU	ANSI/ASME B1.1 THREAD (FEMALE)	CONNECTION	TIGHTENING TORQUE NM (LBF•FT)	MAXIMUM RECOMMENDED PRESSURE
11335	7/16" - 20 UNF	1/4" SAE	11 ÷ 14 (8 ÷ 10)	140 BAR
11336	5/8" - 18 UNF	3/8" SAE	20 ÷ 25 (15 ÷ 18.5)	
11337	3/4" - 16 UNF	1/2" SAE	34 ÷ 47 (25 ÷ 34.5)	
11338	7/8" - 14 UNF	5/8" SAE	54 ÷ 75 (40 ÷ 55)	

SKU	MODEL	PRICE
00000011335	DOUBLE ROTATING UNION - 1/4" SAE	€7.65 VAT EXCLUDED
00000011336	DOUBLE ROTATING UNION - 3/8" SAE	€9.4 VAT EXCLUDED
00000011337	DOUBLE ROTATING UNION - 1/2" SAE	€10.1 VAT EXCLUDED
00000011338	DOUBLE ROTATING UNION - 5/8" SAE	€13.2 VAT EXCLUDED


Sku 11335






Double Rotating Union

Sku 11336



Sku 11337



Sku 11338

