SEALING THREAD IN P.T.F.E.

Dynamic sealing

Product informations

Dynamic sealant adaptable to all thread sizes and materials, built in pure P.T.F.E. 100%.

Product features

- chemically resistant to almost all chemicals and gases (oils, solvents, fuels, LPG, methane, steam, food liquids and drinking water)
- it does not melt and does not burn
- remains soft over time

LENGTH

Technical Features

FUNCTIONAL STABILITY	- 200°C ÷ + 240°C
OPERATING PRESSURE AT ROOM TEMPERATURE	100 BAR
MELTING POINT	330°C ÷ 345°C
LENGTH	175 M
SUGGESTED QUANTITY	1/2 "12 TO 18 WRAPS AND 1 1/2" 16 TO 24 WRAPS

TECNOGAS
I percorsi della tecnologia.
Via Marco Polo 33
35020 Albignasego
Padova – Italy
P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Sealing Thread in P.T.F.E.

SKU	MODEL	PRICE
00000050309	THREAD SEALANT	€38.8 VAT EXCLUDED



Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net