



## ANAEROBIC SEALANT

Medium resistance

### Product informations

Medium resistance anaerobic metal sealant, designed for locking nuts, bolts and other threaded parts that require possible "disassembly".

### Product features

- it can also be used on greasy surfaces
- equipped with a high resistance to corrosion, vibrations, water, gases, oils, fuels and chemical agents
- suitable for use with potable water

**NB.** To seal PVC, PP or Nylon fittings, **use only P.T.F.E. based sealant** (SKU 50950 / 50951) by **pre-treating** the plastic threads with **the activator** (SKU 50959), **screw and tighten within 1 minute** (longer waiting times can break the sealant film that is already forming. **Do not use the thread sealer** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.

### Technical Features

MAX Ø FOR USE M26 - CLEARANCE 0,25 MM	
COLOUR	BLUE
DETECTION	FLUORESCENT IN BLUE LIGHT
FLASH POINT	> 100°C



## Anaerobic Sealant

<i>MANIPULATION</i>	10 - 20 MINUTES
<i>FUNCTIONAL HARDENING TIME</i>	1 - 3 HOURS
<i>FINAL HARDENING TIME</i>	3 - 6 HOURS
<i>TEMPERATURE RANGE</i>	- 55°C ÷ + 200°C

SKU	MODEL	PRICE
00000050308	ANAEROBIC SEALANT 55-03 - 50 ML	€35.0 VAT EXCLUDED
00000050312	ANAEROBIC SEALANT 55-03 - 250 ML	€121.2 VAT EXCLUDED

