ANAEROBIC SEALANT

Medium resistance

Product informations

Medium resistance anaerobic metal sealant, designed for locking nuts, bolts and other threaded parts that require possible "disassembly".

Product features

- it can also be used on greasy surfaces
- equipped with a high resistance to corrosion, vibrations, water, gases, oils, fuels and chemical agents
- suitable for use with potable water

NB. To seal PVC, PP or Nylon fittings, ***use only P.T.F.E. based sealant*** (*SKU 50950 / 50951*) by ***pre-treating*** the plastic threads with ***the activator*** (*SKU 50959*), ***screw and tighten within 1 minute*** (longer waiting times can break the sealant film that is already forming. ***Do not use the thread sealer*** on ABS and polycarbonate threads, for other types of materials ask in advance for our technical opinion.

Technical Features

MAX Ø FOR USE M26 - CLEARANCE 0,25 MM	
COLOUR	BLUE
DETECTION	FLUORESCENT IN BLUE LIGHT
FLASH POINT	> 100°C

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Anaerobic Sealant

MANIPULATION	10 - 20 MINUTES
FUNCTIONAL HARDENING TIME	1 - 3 HOURS
FINAL HARDENING TIME	3 - 6 HOURS
TEMPERATURE RANGE	- 55°C ÷ + 200°C

SKU	MODEL	PRICE
00000050308	ANAEROBIC SEALANT 55-03 - 50 ML	€35.0 VAT EXCLUDED
00000050312	ANAEROBIC SEALANT 55-03 - 250 ML	€121.2 VAT EXCLUDED



TECNOGAS
I percorsi della tecnologia.
Via Marco Polo 33
35020 Albignasego
Padova – Italy
P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net