



Catalogues and Products > Heating > Filters, Valves and Solenoid Valves for Diesel Oil > **Solenoid Valve for Diesel Oil**

SOLENOID VALVE FOR DIESEL OIL

Model M15-1

Product informations

Automatic sectioning valve, electrically operated for diesel fuel (opens when energized and closes when removed); this type of solenoid valve is able to operate continuously even in ring circuits with a pressure differential between upstream and downstream from 0 to 4 bar.

Product features

- the construction is made up of viton sealing elements and with all parts in contact with the fluid made of brass and stainless steel
- the valve remains open only in the presence of electricity
- the instantaneous opening and closing allows the application of this solenoid valve even where a precise dosage of fluids is required

Technical Features

USE	DISEL OIL
OPERATING TEMPERATURE	- 5°C ÷ + 60°C
POWER SUPPLY	230 V / 50 - 60 HZ (SINGLE-PHASE ONLY, THE APPLIANCE DOES NOT WORK IF POWERED WITH THREE-PHASE VOLTAGE)



Solenoid Valve for Diesel Oil

MAXIMUM WORKING PRESSURE	4 BAR
PASSAGE	5,6 MM
PROTECTION	IP65 (PROTECTED AGAINST JETS OF WATER PUMPED FROM ANY DIRECTION AND COMPLETELY SEALED AGAINST DUST AND FUMES)
THREADED CONNECTIONS	<ul style="list-style-type: none"> • DN 10 (SKU R01165) • DN 15 (SKU R01164)

SKU	MODEL	PRICE
00000R01164	SOLENOID VALVE M15-1 - Ø 1/2" FF - 230 V	€75.2 VAT EXCLUDED
00000R01165	SOLENOID VALVE M15-1 - Ø 3/8" FF - 230 V	€75.2 VAT EXCLUDED

