DOUBLE MEMBRANE STABILIZER WITHOUT FILTER

FRG/2MT model, maximum pressure 500 mbar

Product informations

Device which supplies a preset and constant “downstream” pressure value, when the inlet pressure and/or the flow rate changes.

Equipped with

- spring for adjusting the output pressure
- safety membrane
- inlet and output pressure tap for output pressure control
- incorporated filter organ

Technical Features

USE	NOT AGGRESSIVE GASES OF THE THREE FAMILIES (MANUFACTURED / NATURAL / LPG)
INLET PRESSURE RANGE	400 ÷ 500 MBAR
OUTPUT PRESSURE RANGE	16 TO 60 MBAR
FILTER SURFACE	2810 MM^2
FILTER ORGAN	50 M FILTRATION

TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

Double Membrane Stabilizer without Filter

INLET CONNECTION	• 1/2" FF - ***SKU 40031*** • 3/4" FF - ***SKU 40032*** • 1" FF - ***SKU 40033***
OUTPUT CONNECTION	• 1/2" FF - ***SKU 40031*** • 3/4" FF - ***SKU 40032*** • 1" FF - ***SKU 40033***
PRESSURE TAP	ACCORDING TO UNI 8979
OPERATING TEMPERATURE	- 15°C ÷ + 60°C
MATERIAL	DIE-CAST ALUMINUM
DIMENSIONS	120 X 152 MM (AXB)

SKU	MODEL	PRICE
00000040031	DOUBLE DIAPHRAGM STABILIZER FRG/2MT MODEL - 1/2" FF CONNECTIONS	€64.9 VAT EXCLUDED
00000040032	DOUBLE DIAPHRAGM STABILIZER FRG/2MT MODEL - 3/4" FF CONNECTIONS	€63.65 VAT EXCLUDED
00000040033	DOUBLE DIAPHRAGM STABILIZER FRG/2MT MODEL - 1" FF CONNECTIONS	€66.8 VAT EXCLUDED







Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net