# STANDARD BLUE KIT

The complete boiler-saver kit

## Product informations

***BLUE KIT STANDARD*** consists of the *MagBlue Mini* magnetic filter (*SKU 70045*), the *DosaBlue One* polyphosphate dispenser (*SKU 70874*), the Neutral Acid Water 35K neutralizing cartridge and the *LiquidBlue 100* anti-scaling anticorrosive liquid (*SKU 70085*).

## Technical Features

| *SKU 70045* | |
|---|---|
| *MAXIMUM WORKING PRESSURE* | 10 BAR |
| *WORKING TEMPERATURE* | 0 ÷ 90°C |
| *LOAD LOSS* | 0,2 BAR |
| *MAXIMUM HOURLY FLOW* | 1,3 $M^3$/H |
| *MAGNETIC FLUX DENSITY* | 12800 GAUSS |
| *FILTRATION DEGREE* | 300 - 800 ?M |
| *MAGNET* | NEODIMIO |
| *CONNECTIONS* | 3/4" |


Via Marco Polo 33
35020 Albignasego
Padova – Italy
P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

| SKU 70874 | |
|---|---|
| *90° CONNECTIONS* | IN/OUT 1/2" MOBILE |
| *MAX FLOW RATE* | 1,5 $M^3$/H |
| *MAX PRESSURE* | 3,5 BAR |
| *WORKING TEMPERATURE* | 0°C - 45°C |
| *RECHARGE AUTONOMY* | 12 - 15 $M^3$ |
| *PRESSURE DROP* | 0,2 BAR |
| *VASE MATERIAL* | SAN |

| SKU 70894 | |
|---|---|
| *VALID FOR BOILERS UP TO 35 KW* | |
| *LENGTH* | 220 MM |
| *DIAMETER* | 47 MM |
| *MAX PRESSURE* | 0,5 BAR |
| *MAXIMUM TEMPERATURE* | 60°C |
| *MAX CAPACITY* | 8 L/H |
| *UNIT MATERIAL* | PP |
| *HOSE HOLDER MATERIAL* | PP |
| *MATERIAL FIXING SYSTEM* | PP |
| *NEUTRALIZING CHARGE IN CALCIUM CARBONATE ($CACO_3$)* | |
| *EPDM HYDRAULIC SEALS* | |



TECNOGAS
I percorsi della tecnologia.

Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

| *SKU 70894* | |
|---|---|
| *ACCESSORIES* | • PAIR OF 3/4" STRAIGHT HOSE CONNECTORS<br>• FIXING CLIP WITH Ø 50 MM SCREWS |

| *SKU 70085* | |
|---|---|
| *CATEGORY* | AUXILIARY CHEMICAL PRODUCT FOR WATER TREATMENT |
| *APPLICATION* | BIOCIDAL ANTI-CORROSION ANTISCALANT FOR CLOSED CIRCUITS |
| *APPEARANCE* | LIQUID |
| *COLOR* | AMBER |
| *PH* | 6,8 |
| *RELATIVE DENSITY* | 1,06 |
| *WORKING TEMPERATURE* | FROM 10°C TO 130°C |
| *SOLUBILITY WATER* | SOLUBILE |
| *WATER COMPATIBILITY* | • MAKE-UP WATERS WITH LIMITED HARDNESS LEAKS<br>• MEDIUM HARD WATER<br>• SOFTENED OR DEMINERALISED WATER |
| *DOSAGE* | IT CAN BE INTRODUCED INTO THE SYSTEM VIA THE DOSING PUMP, FEED TANK OR OTHER CONVENIENT POINT IN THE CIRCUIT. THE OPTIMAL DOSAGE FOR CORRECT SYSTEM PROTECTION IS *1 LITER FOR EVERY 100 LITERS OF WATER IN THE HEATING SYSTEM.* |
| *1 L JUG (1 KG)* | |



TECNOGAS
I percorsi della tecnologia.
Via Marco Polo 33
35020 Albignasego
Padova – Italy
P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net

# Standard Blue Kit

| SKU | MODEL | PRICE |
|---|---|---|
| 00000070078 | STANDARD BLUE KIT | €176.9 VAT EXCLUDED |






Via Marco Polo 33
35020 Albignasego
Padova – Italy

P.IVA: 03859580288
Tel: +39 049 8625910
Mail: info@tecnogas.net