



TWO STAGE VACUUM PUMP

Model RL2

Product informations

Two-stage pump Mod. **RL2** compact and lightweight, equipped with high quality components and an updated technology that maintains the high performance of the two stage rotating vane pump even at maximum load, making sure that the vacuum is reached in a short time.

Product features

- gas ballast valve
- internal oil circulation for optimum lubrication
- easy reading of the oil level
- large oil filler entrance for easy and clean filling of oil
- filter reduces oil mist at the safety nozzle
- stable and ergonomic handle
- integrated on/off switch against damage and unintentional operation

Technical Features

<i>FLOW RATE</i>	35 L/MIN
<i>FINAL VACUUM WITH CLOSED BALLAST</i>	15 MICRON - 0,02 BAR
<i>POWER SUPPLY</i>	220 - 240 V 50/60 HZ
<i>MINIMUM OIL TEMPERATURE FOR COLD START</i>	+ 5°C
<i>CARTER CAPACITY</i>	125 ML



Two Stage Vacuum Pump

MOTOR POWER	0,16 KW - 2400 ROTATION/MIN
SOUND LEVEL	70 DB(A)
PROTECTION CLASS	I
CONNECTIONS	1/4" SAE
MATERIAL	STEEL
DIMENSIONS	271X167X195 MM (WXDXH)
WEIGHT	3,800 KG

SKU	MODEL	PRICE
00000011420	RL2	€471.87 VAT EXCLUDED
00000011474	SPARE VACUUM GAUGE WITH RADIAL CONNECTION WITHOUT SAFETY VALVE - Ø 80 MM	€28.4 VAT EXCLUDED
00000011479	TAP KIT FOR VACUUM GAUGE	€56.14 VAT EXCLUDED





Two Stage Vacuum Pump

