



## VACUUM PUMP

Model DS PRO EX-2

### Product informations

**DS PRO EX-2**, the vacuum pump designed to achieve high vacuum levels in systems operating with class A2L (R32) or A3 (R290) refrigerant gases; this device is to be used only in well-ventilated environments.

### Product features

- equipped with a vacuum gauge but not solenoid valve
- equipped with a 5 m long tube with ballast valve necessary for evacuation of gases or vapors generated in the early stages of vacuum
- 5-meter long power cable to ensure operator safety

PUMP COMPONENTS	
1	DISCHARGE PIPE WITH BALLAST VALVE
2	VACUUM GAUGE
3	OIL TANK
4	OIL LEVEL SIGHT GLASS
5	OIL DRAIN PLUG
6	HANDLE
7	SUCTION FITTING



## Vacuum Pump

PUMP COMPONENTS	
8	ATEX SWITCH
9	ELECTRIC MOTOR
10	COOLING FAN COVER
11	BASE

## Technical Features

<b>ELECTRICAL SPECIFICATIONS</b>	230V 50-60 HZ
<b>POWER</b>	3/4HP
<b>FLOW RATE</b>	170 L/MIN
<b>ULTIMATE VACUUM</b>	7,5 MICRONS
<b>OIL CAPACITY</b>	600 ML
<b>WORKING TEMPERATURE</b>	5°C ~ 40°C
<b>CONNECTIONS</b>	1/4" E 3/8" SAE
<b>USABLE GAS</b>	A2L-CLASS REFRIGERANTS, INCLUDING R290
<b>WEIGHT</b>	17,9 KG
<b>DIMENSIONS</b>	457X356X254 MM (WXHxD)

SKU	MODEL	PRICE
00000011190	VACCUM PUMP MOD. DS PRO EX-2 - 1 PCS.	€1176.0 VAT EXCLUDED



## Vacuum Pump

