



Catalogues and Products > Heating > Meters for Water > **Whirlpool Meter**

## WHIRLPOOL METER

Removable drum axial woltmann meter

### Product informations

Woltmann meter with epoxy powder coated cast iron body, direct reading on numbered rolls and ring that can be rotated at 360°C.

### Product features

- for use with irrigation water (even unfiltered with small suspended bodies) and for the industrial sector
- with magnetic drive transmission
- pressure drops reduced to a minimum, thanks to the free flow meter
- removable and interchangeable measuring group
- temperature class T30
- possibility of horizontal, vertical or inclined installation
- metal lid with the possibility of closing with a padlock
- MID homologated
- Temperature range: -15°C÷+55°C

### Technical Features



## Whirlpool Meter

SKU	DIAMETER (MM)	PERMANENT FLOW RATE Q <sub>3</sub> (M <sup>3</sup> /H)	OVERLOAD FLOW RATE Q <sub>4</sub> (M <sup>3</sup> /H)	MINIMUM FLOW RATE Q <sub>1</sub> [MPE ±5%] (M <sup>3</sup> /H)	MINIMUM READING UNIT (L)
70550	Ø 50 MM	63	78,75	0,63	0,5
70551	Ø 65 MM	63	75,75	0,63	0,5
70552	Ø 80 MM	100	125	1	0,5
70553	Ø 100 MM	160	200	1,6	5
70554	Ø 150 MM	250	312,5	2,5	5

SKU	MODEL	PRICE
00000070550	WHIRLPOOL METER - L. 200 MM - DN 50	€641.55 VAT EXCLUDED
00000070551	WHIRLPOOL METER - L. 200 MM - DN 65	€721.8 VAT EXCLUDED
00000070552	WHIRLPOOL METER - L. 225 MM - DN 80	€770.1 VAT EXCLUDED
00000070553	WHIRLPOOL METER - L. 250 MM - DN 100	€898.8 VAT EXCLUDED
00000070554	WHIRLPOOL METER - L. 300 MM - DN 150	€1414.7 VAT EXCLUDED

